




CHAIN


Commercial quality, galvanised, short link, DIN 766



part number	diameter	internal length (B)	external width(C)	weight per metre
4463-904	4 mm	16.0 mm	14 mm	0.32 kg
4463-906	6 mm	18.5 mm	20 mm	0.75 kg
4463-908	8 mm	24.0 mm	26 mm	1.35 kg
4463-910	10 mm	28.0 mm	34 mm	2.25 kg
4463-913	13 mm	36.0 mm	44 mm	3.80 kg

CHAIN

Commercial quality, galvanised, long link, DIN 766





part number	diameter	internal length (B)	external width (C)	weight per metre
4464-004	4 mm	32.0 mm	16 mm	0.27 kg
4464-005	5 mm	36.0 mm	20 mm	0.43 kg
4464-006	6 mm	42.0 mm	24 mm	0.63 kg
4464-008	8 mm	52.0 mm	32 mm	1.10 kg
4464-010	10 mm	66.0 mm	40 mm	1.75 kg
4464-013	13 mm	82.0 mm	50 mm	2.95 kg

CARABINE HOOKS

Galvanised

type (AxB)	breaking strength
6 x 60	120 kg
8 x 80	230 kg
10 x 100	350 kg

(Also available in stainless steel)



ALSO AVAILABLE:
Victor chain




Rope- coils and reels



GALVANISED COMMERCIAL BOW SHACKLES

(not for lifting purposes)

Breaking strength	Bow diameter (a)	Pin diameter (b)	width (d)	Inside length(e)
0.08 t	5 mm	5 mm	10 mm	19 mm
0.1 t	6 mm	6 mm	13 mm	25 mm
0.2 t	8 mm	8 mm	16 mm	32 mm
0.3 t	10 mm	10 mm	19 mm	38 mm
0.4 t	11 mm	11 mm	22 mm	46 mm
0.5 t	12 mm	12 mm	25 mm	51 mm
0.6 t	14 mm	14 mm	28 mm	58 mm
0.8 t	16 mm	16 mm	32 mm	64 mm
1.1 t	20 mm	20 mm	38 mm	76 mm
1.5 t	22 mm	22 mm	44 mm	89 mm
2.0 t	25 mm	25 mm	51 mm	100 mm
2.6 t	28 mm	28 mm	57 mm	115 mm
3.2 t	32 mm	32 mm	64 mm	127 mm
4.5 t	38 mm	38 mm	76 mm	146 mm


GALVANISED COMMERCIAL DEE SHACKLES

(not for lifting purposes)

Breaking strength	Bow diameter (a)	Pin diameter (b)	width (d)	Inside length(e)
0.08 t	5 mm	5 mm	10 mm	19 mm
0.1 t	6 mm	6 mm	13 mm	25 mm
0.2 t	8 mm	8 mm	16 mm	32 mm
0.3 t	10 mm	10 mm	19 mm	38 mm
0.4 t	11 mm	11 mm	22 mm	46 mm
0.5 t	12 mm	12 mm	25 mm	51 mm
0.6 t	14 mm	14 mm	28 mm	58 mm
0.8 t	16 mm	16 mm	32 mm	64 mm
1.1 t	20 mm	20 mm	38 mm	76 mm
1.5 t	22 mm	22 mm	44 mm	89 mm
2.0 t	25 mm	25 mm	51 mm	100 mm
2.6 t	28 mm	28 mm	57 mm	115 mm
3.2 t	32 mm	32 mm	64 mm	127 mm
4.5 t	38 mm	38 mm	76 mm	146 mm

